SDS INSULCON CEMENTO CONCRETE FINISH - GREY

Statement of Hazardous Nature Hazardous According to Worksafe Australia Criteria

Supplier:

Insulcon Pty Ltd, ABN 96 887 479 796 34 Swift Way, Dandenong South VIC 3175 Phone: (03) 9768 2335 | Fax: (03) 9768 2337



Identification:

Product Name: Insulcon Cemento Concrete Finish – Grey
Recommended Use: Decorative and protective cement-based finish

UN No:

Hazchem:

None allocated

Physical Description / Properties

Appearance: Fine dark grey powder

Vapour Pressure: Not applicable
Specific gravity: Approx. 1.5
Flash point: Non-combustible

Solubility in water: Partially soluble, alkaline slurry

pH (wet): Alkaline

Ingredients

Portland Cement 15-40%Calcium Hydroxide (Lime) 1-10%Calcium Carbonate 30-55%Fly Ash (may contain silica) 1-5%Talc (may contain silica) 1-10%

Ingredients not listed are considered non-hazardous or present below disclosure thresholds under WHS Regulations. Exact percentages are withheld as trade secrets. Product may contain trace amounts of respirable crystalline silica (<0.1%).

MSDS INSULCON TEXTURE

HEALTH HAZARD INFORMATION

Acute overexposure:

Swallowed: May cause abdominal discomfort, irritation of mouth and throat.

Eyes: Causes serious eye irritation on direct contact.

Inhalation: Dust inhalation may cause coughing, throat irritation and respiratory discomfort.

Skin: May cause irritation and drying of skin.

Chronic: Prolonged or repeated inhalation of dust containing crystalline silica may cause lung

disease (silicosis). Repeated skin exposure may cause dermatitis.

FIRST AID MEASURES

If swallowed: Rinse mouth and drink water. Do not induce vomiting. Seek medical attention. If in Eyes: Flush with plenty of water for 15 minutes. Seek immediate medical attention

If on skin: Wash thoroughly with soap and water. Remove contaminated clothing. Seek medical

advice if irritation persists.

If Inhaled: Move person to fresh air. Seek medical attention if symptoms persist.

Advice to doctor: Treat symptomatically

PRECAUTIONS FOR USE

Engineering Controls: Use only in well-ventilated areas to minimise dust exposure.

Personal Protection:

Eyes: Safety glasses with side shields or goggles (AS/NZS 1336)..

Skin: Gloves, protective clothing. Wash thoroughly after use.

Respiratory: P2 respirator or equivalent when handling powder.

SAFE HANDLING INFORMATION

Handling and Storage: Store in sealed containers, in a cool dry place. Protect from moisture..=

Spills and Disposal: Avoid dust. Contain spill with minimal dust generation. Collect and dispose of in

accordance with local regulations. Do not allow to enter sewers, storm water drains or

open water.

Fire / Explosion hazard

Product is non-flammable.

CONTACT POINT

Technical Manager Insulcon Pty Ltd.

This MSDS summarises our best knowledge of the health and safety hazards associated with this product. Each user should read this MSDS and consider the data in terms of how the product will be used in the workplace.

VALIDITY OF ISSUE

This MSDS is valid until 02/09/2030